

## PRODUCTBLAD

## E95- E10

Property		Unit	Minimum	Maximum	Test method
Research Octane Number (RON)		-	59,0	-	EN ISO 5164
Motor Octane Number (RON)		-	85,0	-	EN ISO 5163
Load content		mg/l	-	5,0	EN 237
Density at 15 °C		kg/m <sup>3</sup>	720	775,0	EN ISO 13675
Sulfur content		mg/kg	-	10,0	EN ISO 20846
Manganese content		mg/l	-	2,0	EN 16315 / EN 16136
Oxidation stability		min.	360	-	EN ISO 7536
Existent gum content (Solvent washed)		mg/100ml	-	5	EN ISO 6246
Copper strip corrosion (3 hrs. at 50 °C)		Rating	Class 1		EN ISO 2160
Appearance		-	Clear and bright		Visual inspection*
Hydrocarbon type content	Olefins	% v/v	-	18,0	EN ISO 22854
	Aromatics	% v/v	-	35,0	
Benzene content		% v/v	-	1,0	EN 238
Oxygen content		% m/m	-	3,7	EN 1601
Oxygenates content	Methanol			3,0	EN 1601
	Ethanol			10,0	
	iso-propyl alcohol			12,0	
	iso-butyl alcohol			15,0	
	tert-butyl alcohol			15,0	
	ether (5 or more C atoms)			22,0	
	other oxygenates			15,0	
Vapour pressure	Summer**	kPa	45,0	60,0	EN ISO 13016-1
	Winter***	kPa	65,0	95,0	
Vapour Lock Index	April + October	index	-	1214	
Distillation	% evaporated at 70 °C E70**	% v/v	22,0	50,0	EN ISO 3405
	% evaporated at 70 °C E70***	% v/v	24,0	52,0	
	% evaporated at 100 °C E100	% v/v	46,0	72,0	
	% evaporated at 150 °C E150	% v/v	75,0	-	
	Final Boiling Point FBP	°C	-	210	
	Distillation residue	% v/v	-	2	

\* Appearance shall be determined at ambient temperature

\*\* Summer: May 1st - September 30th

\*\*\* Winter: October 1th - April 30th

Edition: 2019

Version: 1