

PRODUCT SHEET

CLEARSPRAY

FullTank ClearSpray is an additive urea solution (32.5% urea) that can be used in vehicles equipped with SCR technology. The urea solution helps reduce the emissions of harmful nitrogen oxides (NOx). ClearSpray meets the purity specifications as prescribed in ISO-22241. These specifications are listed in the table below.

Advantages

- ClearSpray reduces the risk of problems that can occur in the catalyst due to the use of urea solutions. The presence of a non-foaming additive ensures optimal atomization. This minimizes blockages of the SCR catalyst.
- ClearSpray is extremely suitable for vehicles where the optimal temperature required for proper functioning of the standard product is not always achieved.

Properties	Unit	Minimum	Maximum
Urea content	% (m/m)	31,8	33,2
Density (20°C)	kg/m	1087,0	1093,0
Biuret	% (m/m)	-	0,3
Aldehydes	mg/kg	-	5
Phosphate	mg/kg	-	0,5
Insoluble particles	mg/kg	-	20
Calcium	mg/kg	-	0,5
Iron	mg/kg	-	0,5
Copper	mg/kg	-	0,2
Zinc	mg/kg	-	0,2
Chrome	mg/kg	-	0,2
Nickel	mg/kg	-	0,2
Aluminium	mg/kg	-	0,5
Magnesium	mg/kg	-	0,5
Sodium	mg/kg	-	0,5
Potassium	mg/kg	/	0,5
Identity (infrared)	-	Identical to reference	